

5D-HD400 HEVC/H.265 HD DECODER

FEATURES:

- 4 IP (MPTS/SPTS) input
- Support H.265/H.264/MPEG2 video decoding
- Support MPEG1 Layer 2, LC-AAC, HE-AAC, AC3 (2.0) audio decoding
- 4 HDMI decoding out
- Control via web management



TECHNICAL SPECIFICATIONS:

Model		5D-HD400
Input	IP	4 IP (100M/1000Mbps Ethernet, RJ45, UDP&RTP protocol, Unicast/multicast)
	Max bitrate	≤300Mbps
Decoding	Video Format	HEVC/H.265, MPEG-4 AVC/H.264, MPEG-2, AVS, AVS+
	Video Resolution	1920×1080_60p/50p, 1920×1080_60i/50i, 1280×720_60p/50p, 480p, 480i, 576p, 576i,
	Audio Format	MPEG 1 Layer2, LC-AAC, HE-AAC, AC3 (2.0)
	Audio Channel	One stereo audio embedded in each port
Output		4 HDMI decoding out
General	Mains supply voltage	220VAC ±10% , 50/60Hz
	Consumption	25W
	Dimensions	44mm(H) x 482mm(W) x 328mm(D)
	Weight	4kg
	Temperature	0~45°C (operating), -20~80°C (storage)