

DVBS-IP800R DVB-S2 RECEIVER MULTIPLEXER

FEATURES:

- Reception of FTA DVB-S/S2 programs
- Integrated demodulating and multiplexing functions
- 8 DVB-S2 tuner and 1 ASI input
- ASI and IP (MPTS) output
- Multiplex up to 8 channels tuner and 1 ASI input to one MPTS
- Huge buffer memory for saving the overflowing code stream
- LCD display and control setting on front panel
- Support Web "NMS"



TECHNICAL SPECIFICATIONS:

Model		DVBS-IP800R
Input section	DVB-S2	8x tuner, 950~2150MHz, symbol rate: QPSK 1~45MS/s and 8PSK 2~30MS/s (F connector)
	ASI	1x ASI, 188/204 package format (BNC interface)
Re-multiplex		PID re-mapping
		PCR accurate adjusting
		Automatic generating PSI/SI table
Output section	IP	MPTS over UDP, RTP/RTSP output as mirror of ASI output, 1000Mbps Ethernet (max 280mbps), RJ45 port
	ASI	2x ASI (max 180Mbps)
	Output PID range	0x0000-0x1FFF
	PID transparent	Any PID transparent and mapping achievable
	Amount of output PID per input	128
General	Mains supply voltage	AC220V ±10%, 50/60Hz (AC110V optional)
	Consumption	18W
	Dimensions	44mm(H) x 482mm(W) x 300mm(D)
	Weight	3.5kg
	Temperature	0~45°C (operating), -20~80°C (storage)